CADDY LG LED


Architectural Outdoor







FEATURES



- Tempered Clear Glass Diffuser
- · Surge Protector
- Fully Gasketed
- Mounts Direct to Flat Surface w/ Three #8 Wall Anchors (Not Included)
- CSA Listed Wet Location For Wall Mount (Down Light Only)

PROJECT: TYPE:

COMMENTS:


PO#:


- · Dark Sky Compliant
- Emergency Battery Available
- · LED Light Fixture



LINE DRAWING

QTY:





Matte

Silver

Textured

White



FINISHES

Antique

Copper

Steel

Swedish









Metallic



Sand



For RAL Colors & Custom Match -**Contact Teron** Lighting Inc.





CADDY LG LED

Architectural Outdoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core

Tixture dore				
PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER	
CDL - Caddy LG	L48.0 - 48W @ 1050mA 0-10V Dimming Driver	120 - 277V	0-10V Dimming	
ORDER INFO				
CDL	L48.0	120 - 277V	Not Applicable	

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	AC - Antique Copper AS - Antique Silver BT - Bronze Mist MB - Metallic Black SM - Matte Silver SN - Sand SW - Swedish Steel TB - Textured Bronze (Standard) TW - Textured White	30K - 3000K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	EBC - 6W Integral EM Battery (-20°C) Available EBCA12 - Title 20 Compliant 12 Watt Integral Battery EBW - 5.1W Emergency Battery Available F - Fused PCL - Photocell SPD - Surge Protection Device MSE - Motion Sensor External
ORDER INFO			
Not Applicable	AC	30K	DIM

Example ^ (may not represent a manufacturable product)

PROD	SOURCE	30K SPECS		
CDL	L48.0	30K SPECS 30K - 3000K Color Temp 6283 LED Source Lumens 130 LED Source Lumens Per Watt		

REPLACEMENT PART	PART NO	NOTES
Clear Termpered Glass Lens (Standard)	37050	Don't see the configuration you are looking for? Call us today at (513) 858-6004



Example ^ (may not represent a manufacturable product)